

Galaxy 1500

Cord-Electric Burnisher

GENERAL	The machine shall be a 20-in (51 cm) cord-electric, high speed floor burnisher. The machine shall have a two-piece design, shipped in two boxes and able to be sent by parcel carrier.
CONSTRUCTION	The machine shall have a stamped steel skirt with a non-marking vinyl bumper. The base shall consist of 11-gauge steel. The base and skirt shall be chrome-plated.
PAD	The machine shall have a pad speed of 1500 RPM.
LOCKOUT	The machine shall have a mechanical lockout lever located in the center of the switch box, which must be depressed before the switch lever will activate.
CORD	The cord shall be connected to the handle box. It shall be 50-ft (15.2 m) long, 14-3 ST, safety yellow with a heavy-duty plug.
WHEELS	The wheels shall have a 5-in (12.7 cm) diameter, be 1.375-in wide, and consist of non-marking gray rubber. The machine shall have mounted at the rear two wheels which will assist in transport.
MOTOR	The motor shall be 66-frame, 1.5 HP. It shall be a permanent magnet type, DC, full wave bridge rectified motor. The motor cap shall be chrome-plated for durability.
TRANSMISSION	The pad driver shall be driven by a heavy-duty V-belt.
DIMENSIONS	Weight: 97 lbs (44 kg) Length: 27 in (68.6 cm) Height: 46 in (117 cm) Width: 21 in (53.3 cm)
SOUND LEVEL	The machine shall operate at 69 dBA.
ISO 9000	The manufacturer must be ISO 9001 registered.
WARRANTY	The machine shall carry a 3-year warranty against defects in material and workmanship. Labor shall be carried for 1 year.

Features & Benefits

Demonstration Guide

Competitive Comparison

Bid Specifications

Recommended Parts Stock

Supplemental Price List



Integrity at work.®