



Bid Specs For The

pony 20 SCA

GENERAL	The machine shall be a self-contained, motor-propelled, walk behind carpet extractor with a 22-in. (56 cm) cleaning path.
CAPACITIES	The solution tank shall be 20 gal. (75.8 l.) with a solution level indicator. The recovery tank shall be 20 gal. (75.8 l.) and capable of draining into 5 gallon buckets, a toilet or floor drain.
SOLUTION PUMP	The machine shall have a 100 PSI solution pump, diaphragm, bypass-type, and sealed for protection against water damage. The solution pump shall have viton seals/valves to extend life where delimonene solvents are used.
VACUUM MOTOR	The machine shall have a 3-stage, bypass-type motor. The motor shall be 115V. (240V. available), 1.75 HP (1400 watts) and have a closed waterlift of 125 in. (317.5 cm).
DRIVE MOTOR	The machine shall have a 115V. (240V. available) .05 HP variable-speed drive gear motor.
CONSTRUCTION	The machine shall be constructed of roto-molded polyethylene tanks, mounted on a welded steel epoxy powder-coated corrosion resistant base.
SPRAY JETS	The machine shall have 5 stainless steel snap-in/snap-out spray jets mounted in a spray manifold. The manifold shall be easy to slip out and removable for jet inspection, cleaning and replacement.
MOUNTING	The machine shall have two 8-in. (20 cm) diameter wheels. The wheels shall be roller-bearing type with grooved non-marking gray rubber tread. The machine shall have two 4-in. (10 cm) diameter casters. The casters shall be ball-bearing swivel type.
BRUSH	The machine shall have a 22-in. (56 cm) cylindrical brush that shall be motor-driven through a timing belt.
BRUSH MOTOR	The machine shall have a 115V. (240V. available) .25 HP permanent-magnet type motor, operating at 1,200 RPM.
VACUUM SHOE	The machine shall have a weighted, cast aluminum vacuum head. The vacuum head shall swivel and follow the machine on radius turns. It shall

be adjustable, either floating or locked down. The vacuum head shall be removable for transporting and cleaning.

CORD The machine shall have a 75-ft. (23 m) 12-3 SJT safety yellow cord, detachable via a twist-lock plug.

FLOAT SHUT-OFF The machine shall have a float shut-off mechanism, ball-type.

DIMENSIONS Weight: 165 lbs. (75 kg)
Height: 41 in. (104 cm)
Length: 47 in. (119 cm)
Width: 23.5 in. (60 cm), 27 in. (cm) vacuum shoe

SOUND LEVEL The sound level shall be 72 dbA at the operator position.

MISCELLANEOUS The machine shall have a pre-spray gun, liquid percolator, easy-view clear dome cover, hinged body (for easy access to service drive motor and pump), and removable cover (for service to the brush motor).

ISO 9000 NSS Enterprises, Inc. has been ISO 9001 registered since September 23, 1998.

WARRANTY The machine shall carry a 3-year limited warranty against defects in material and workmanship, and 10 years on its polyethylene body.

NSS[®] Enterprises, Inc.

3115 Frenchmens Road · Toledo, Ohio 43607 USA

PH 419/531 -2121 · FAX 419/531 -3761

Specifications subject to change without notice.