



Bid Specs
For The
predator CX3

GENERAL	The machine shall be a compact, lightweight portable 3-tank carpet spotter, that includes 10-ft. (3.05 m) solution and vacuum hoses and 3.5-in. (9 cm) hand tool.
CONSTRUCTION	The body shall be high density rotocast polyethylene.
RECOVERY TANK	The machine shall have a 2.5-gallon (9.5 l), detachable recovery tank.
SOLUTION TANKS	The machine shall have dual 1-gallon (3.785 l) solution tanks, one each for solution and rinse.
SOLUTION PUMP	The machine shall have a positive-displacement, 55 PSI pump.
VACUUM MOTOR	The machine shall have a 2-stage vacuum motor with 90-in. waterlift.
MOUNTING	The machine shall have two 5-in. (12.75 cm) rear wheels and a folding, built-in handle for easy transportation.
SWITCHES	The machine shall have a master on/off rocker switch plus a tank selector switch.
CORD	A 25-ft. (7.6 m) power cord shall be provided, rated 18-3.
SOUND LEVEL	The machine shall be capable of running at 79 dbA.
DIMENSIONS	Weight: 29 lbs. (13.5 kg) Length: 25" (64cm) Width: 10.5" (26.5 cm) Height: 19" (48.5 cm)
ISO 9000	NSS Enterprises, Inc. has been ISO 9001 registered since September 23, 1998.
WARRANTY	The machine shall have a 1 year limited warranty.

NSS[®] Enterprises, Inc.
3115 Frenchmens Road · Toledo, Ohio 43607 USA
PH 419/531 -2121 · FAX 419/531 -3761
Specifications subject to change without notice.