



Bid Specs For The *mustang*

GENERAL	The machine shall be an electric, 175 RPM floor machine, available in 17 and 20-in. models.
HANDLE	The handle shall be a cylindrical tube and have a 1.5-in. diameter, and made of 14-gauge chrome-plated steel. The handle shall lock into any position within its 75-degree adjustment swing.
LOCKOUT	The machine shall have a mechanical lockout lever located in the center of the switch box, which must be depressed before the switch lever will activate.
CORD	The cord shall be connected to the handle box. It shall be 50-ft. (15.2 cm) long, 14-3 ST, safety yellow with a heavy-duty plug.
WHEELS	The wheels shall have a 5-in. diameter, be 1.375-in. wide, and consist of non-marking gray rubber. They will be positioned in a wide stance to provide easy transport.
MOTOR	The motor shall be AC, 66-frame, 1 HP or 1.5 HP. It shall be a capacitor-start motor covered by an ABS plastic drip cover.
TRANSMISSION	The gears shall be protected by an odum coupling. The gears will be hardened steel with a 11:1 gear ratio. The gear box cover shall not join below the grease level.
BASE/SKIRT	The machine shall have a cast-aluminum base. The skirt shall consist of 11-gauge steel for 20-in. models and 12-gauge steel for 17-in. models, along with a non-marking vinyl bumper. The base and skirt shall be powder-coated.
ACCESSORIES	The machine will be adaptable for carpets and bare floors. It shall be equipped with a single cylindrical tube handle which allows for the use of most solution tanks. The skirt shall also provide an assembled tube for solution feeding to the brush or pad.
DIMENSIONS	Weight: 93 lbs. (42.2 kg) – 17-in. 1 HP 107 lbs. (48.6 kg) – 17-in. 1.5 HP 100 lbs. (45.4 kg) – 20-in. 1 HP 114 lbs. (51.8 kg) – 20-in. 1.5 HP Length: 23.5 in. (59.7 cm) – 17-in. models

24.5 in. (62.2 cm) – 20-in. models
Height: 47 in. (119.4 cm)
Width: 18 in. (46 cm), 21 in. (53 cm)

- UL / ULC LISTING** The machine shall be listed by UL and ULC.
- SOUND LEVEL** The machine shall operate at a quiet 70 dbA.
- ISO 9000** NSS Enterprises, Inc. has been ISO 9001 registered since September 23, 1998.
- WARRANTY** The machine shall carry a 3-year warranty against defects in material and workmanship. Labor shall be carried for 1 year.

NSS® Enterprises, Inc.
3115 Frenchmens Road · Toledo, Ohio 43607 USA
PH 419/531 -2121 · FAX 419/531 -3761
Specifications subject to change without notice.