



## Bid Specs For The

# ***aquaforce*** 1000MXDE

<b>GENERAL</b>	The machine shall be a cart-electric industrial pressure washer with 1000 PSI, able to deliver 2.2 gallons per minute of solution. It shall also accept water up to 180°F.
<b>CONSTRUCTION</b>	The machine shall be constructed of powder-coated steel. The pump is an industrial triplex plunger.
<b>CHEMICAL</b>	The machine shall have dual chemical injection with two 1-gallon chemical jugs.
<b>PROTECTION</b>	The machine shall have a mechanical thermal relief valve, which allows this unit to accept water up to 180°F.
<b>CORD</b>	The machine shall have a 35-ft. (10.7 m) power cord with ground fault circuit interrupter.
<b>PUMP</b>	The machine shall have a positive-displacement, 1000 PSI pump, which includes ceramic plungers with replaceable stainless steel valves, forged crankshaft and roller bearings in oil bath lubrication.
<b>MOTOR</b>	The machine shall have an industrial 1.5 HP, 110V., 15 amp electric motor.
<b>WAND</b>	The machine shall have a 36-in. (91.5 cm) wand with insulated trigger gun and 40-ft. (12.2 m) hose. The wand tip features interchangeable tips.
<b>SWITCHES</b>	One master on/off switch shall be provided.
<b>DIMENSIONS</b>	Weight: 127 lbs. (58.5 kg) Length: 26 in. (66.5 cm) Width: 21.5 in. (55 cm) Height: 40 in. (101 cm)
<b>WARRANTY</b>	The machine shall have a one-year limited warranty.
<b>ISO 9000</b>	NSS Enterprises, Inc. has been ISO 9001 registered since September 23, 1998.

**NSS<sup>®</sup> Enterprises, Inc.**  
3115 Frenchmens Road · Toledo, Ohio 43607 USA  
PH 419/531 -2121 · FAX 419/531 -3761  
Specifications subject to change without notice.