



# Bid Specs For The ***aquaforce*** 1500A

- GENERAL** The machine shall be a compact, hand-carry pressure washer with 1450 PSI, able to deliver 2 gallons per minute of solution.
- CONSTRUCTION** The machine shall be constructed of aluminum with a hardened plastic outer case.
- CORD** The machine shall have a 15-ft. power cord with ground fault circuit interrupter.
- PUMP** The machine shall have a positive-displacement, 1450 PSI pump, which includes ceramic plungers with replaceable stainless steel valves, forged crankshaft and roller bearings in oil bath lubrication.
- MOTOR** The machine shall have an industrial 2 HP, 115V., 19 amp electric motor.
- WAND** The machine shall have a 24-in. wand with insulated trigger gun and 25-ft. hose. The wand tip is adjustable from 0 to 60 degrees.
- SWITCHES** One master on/off switch shall be provided.
- DIMENSIONS** Weight: 50 lbs. (22.7 kg)  
Length: 9 in. (23 cm)  
Width: 15.5 in. (39.5)  
Height: 7 in. (17.8 cm)
- ISO 9000** NSS Enterprises, Inc. has been ISO 9001 registered since September 23, 1998.
- WARRANTY** The machine shall have a one-year limited warranty.

**NSS® Enterprises, Inc.**

3115 Frenchmens Road · Toledo, Ohio 43607 USA

PH 419/531 -2121 · FAX 419/531 -3761

Specifications subject to change without notice.