



Bid Specs For The

aquaforce 2000GCX

GENERAL	The machine shall be a cart-gasoline, medium industrial pressure washer with 2000 PSI, able to deliver 3 gallons per minute of water.
CONSTRUCTION	The frame shall be constructed of powder-coated steel. The pump is a medium duty axial pump.
CHEMICAL	The machine shall have a 3-gallon chemical dispenser tank.
PROTECTION	The machine shall have a mechanical thermal relief valve, which allows this unit to accept water up to 180°F.
PUMP	The machine shall have a positive-displacement, 2000 PSI axial pump, which includes ceramic plungers with replaceable stainless steel valves.
ENGINE	The machine shall have a 5 HP Honda engine with choke control and kill switch. One half-gallon gasoline capacity shall be provided.
WAND	The machine shall have a 36-in. (91.5 cm) insulated wand with trigger gun and 40-ft. (12.2 m) non-marking hose. The wand features multi-reg adjustable tips.
SWITCH	One master on/off switch is provided.
DIMENSIONS	Weight: 92 lbs. (41.7 kg) Length: 26" (66.5 cm) Width: 21.5" (55 cm) Height: 26" (66.5 cm)
WARRANTY	The machine shall have a one-year limited warranty.
ISO 9000	NSS Enterprises, Inc. has been ISO 9001 registered since September 23, 1998.

NSS[®] Enterprises, Inc.
3115 Frenchmens Road · Toledo, Ohio 43607 USA
PH 419/531 -2121 · FAX 419/531 -3761
Specifications subject to change without notice.