



## Bid Specs For The

# ***aquaforce*** 25006HX

<b>GENERAL</b>	The machine shall be a cart-gasoline, industrial pressure washer with 2500 PSI, able to deliver 3.2 gallons per minute of water.
<b>CONSTRUCTION</b>	The frame shall be constructed of powder-coated steel. The pump is an industrial triplex plunger.
<b>CHEMICAL</b>	The machine shall have a 3-gallon chemical dispenser tank.
<b>PROTECTION</b>	The machine shall have a mechanical thermal relief valve, which allows this unit to accept water up to 180°F.
<b>PUMP</b>	The machine shall have a positive-displacement, 2500 PSI adjustable-pressure pump, which includes ceramic plungers with replaceable stainless steel valves, forged crankshaft and roller bearings in oil bath lubrication.
<b>ENGINE</b>	The machine shall have a 6.5 HP Honda engine with choke control, kill switch and oil alert switch. One-gallon gasoline capacity shall be provided.
<b>WAND</b>	The machine shall have a 36-in. (91.5 cm) insulated wand with trigger gun and 40-ft. (12.2 m) non-marking hose. The wand features multi-reg adjustable tips.
<b>SWITCH</b>	One master on/off switch is provided.
<b>DIMENSIONS</b>	Weight: 103 lbs. (46.5 kg) Length: 26" (66.5 cm) Width: 21.5" (55 cm) Height: 26" (66.5 cm)
<b>WARRANTY</b>	The machine shall have a one-year limited warranty.
<b>ISO 9000</b>	NSS Enterprises, Inc. has been ISO 9001 registered since September 23, 1998.

**NSS<sup>®</sup> Enterprises, Inc.**  
3115 Frenchmens Road · Toledo, Ohio 43607 USA  
PH 419/531 -2121 · FAX 419/531 -3761  
Specifications subject to change without notice.