



Mustang 300 DS

Dual-Speed Floor Machine



For a versatile, economical dual-speed floor machine, nothing beats the Mustang 300 DS. Precision-balanced for easy operation and maneuverability, this machine saves time and money by effectively doing the job of two scrubbers—a standard 180 RPM floor machine and a 300 RPM buffer.

- High-speed operation is perfect for polishing, buffing, or damp scrubbing hard floors. The Mustang 300DS can also be used with a bonnet for routine carpet maintenance.
- Low speed operation is used for efficient scrubbing, wet stripping, and polishing in congested areas where greater control is needed.
- A lock-out safety mechanism on the handle prevents unauthorized operation if the machine is left unattended.
- Available in 17 and 20-inch widths, the Mustang 300 DS is ideal for schools, office buildings, and other facilities where appearances need to be kept up while holding equipment costs down.

NSS® Enterprises, Inc.
3115 Frenchmens Road
Toledo, Ohio 43607-2958
USA
www.nss.com



Printed on Green Seal® certified paper that contains 30% recycled post-consumer fiber.

Mustang 300 DS Specifications

Pad or Brush	17 in (43.2 cm), 20 in (50.8 cm)
Motor	
Type	Permanent magnet, DC rectified
HP	1.5 HP (1100 watts)
Size	66 frame
Voltage	110-120V (220-240V available)
Current	15 amps@ 120V, 7.5 amps @ 240V
Gear	3-idler planetary
Pad Speed	
High	300 RPM
Low	180 RPM
Cord	
120V	50 ft (15.2 m) 14-3 ST yellow
240V	75 ft (23 m) 16-3 ST SHUKO safety yellow
Weight (w/ Pad Driver)	
17 in Machine	86 lbs (39 kg)
20 in Machine	93 lbs (42 kg)
17 in Shipping	105 lbs (48 kg)
20 in Shipping	112 lbs (51 kg)
Shipping Class	125
Warranty	3 year limited
Productivity (17 in)	
Polish	7,000 sq ft per hour (650 sq m)
Scrub	2,700 sq ft per hour (251 sq m)
Shampoo	1,200 sq ft per hour (111 sq m)
Spray Buff	2,700 sq ft per hour (251 sq m)
Productivity (20 in)	
Polish	10,000 sq ft per hour (929 sq m)
Scrub	3,600 sq ft per hour (334 sq m)
Shampoo	1,430 sq ft per hour (133 sq m)
Spray Buff	3,100 sq ft per hour (288 sq m)



The Mustang 300 DS features a mechanical lock-out which must be released before the switch lever can be activated. This feature helps prevent unauthorized operation.



NSS Enterprises, Inc.
3115 Frenchmens Road
Toledo, OH 43607-2958
USA

P: (800) 677-1663
F: (419) 531-3761

mailto:mailus@nss.com
www.nss.com

Specifications subject to change without notice.



- 1** Dual switch levers allow the operator to easily control the side-to-side movement of the machine.
- 2** Metal cord strain relief and internal compression lock prevent the cord from being pulled out of the machine.
- 3** Sturdy 1.25-in tube handle is chrome-plated to resist corrosion.
- 4** The rocker switch on the rear of the motor permits easy transition from high speed (300 RPM) to low speed (180 RPM).
- 5** 5-in rear transport wheels make the Mustang 300 DS easy to move to the job site.
- 6** 360° non-marking bumper protects walls

DO NO HARM™

Dual-speeds allow the machine to be used at the speed required to do the job, eliminating wasted effort and energy.

5-in rear transport wheels make the Mustang 300 DS easy to move from job-to-job.

The handle and deck on this machine is recyclable, lessening the environmental footprint of this scrubber.

DISTRIBUTED BY