



# NSS Battery Specification

For correct re-charging procedure, please refer to your machine owner's manual.

Model/ Battery Compartment Size (Inches / Millimeters)	System	Amp Hour	Battery Quantity	Part # (Type)	Approximate Run Time (Hours)	Length (Inches/ Millimeters)	Width (Inches/ Millimeters)	Height (Inches/ Millimeters)	Weight (Pounds/ Kilograms)
<b>Wrangler 1503 AB</b> 10.5 L x 8 W x 7.5 H 267 L x 203 W x 190 L	24V	35	2 x 12V	12-9-184-1 (AGM)	1.5	5.25 / 133	7.5 / 190	7 / 178	22.33 / 10.13
<b>Wrangler 1708-2008 AB /</b> 14 L x 12.5 W x 10 H 355 L x 317 W x 254 H	24V	115	2 x 12V	23-9-211-1 (Wet)	2.5	13.13 / 334	6.75 / 171	9.38 / 238	59 / 27
	24V	100	2 x 12V	23-9-273-1 (Sealed)	2.5	12.09 / 307	6.65 / 169	8.31 / 211	67 / 30
	24V	115	2 x 12V	23-9-282-1 (Dry)	2.5	13.13 / 334	6.75 / 171	9.38 / 238	59 / 27
<b>Wrangler 2016 /</b> 20.5 L x 14.5 W x 10.5 H 521 L x 368 W x 266 H	24V	225	4 x 6V	33-9-036-1 (Wet)	4	10.25 / 260	7.13 / 181	10.5 / 267	64 / 29
	24V	225	4 x 6V	33-9-095-1 (Dry)	3.25	10.25 / 260	7.13 / 181	10.5 / 267	55 / 25
	24V	200	4 x 6V	64-9-193-1 (Sealed)	3.25	10.24 / 260	7.12 / 181	10.83 / 275	59 / 27
	24V	225	4 x 6V	33-9-098-1 (AGM)	3.25				
	24V	130	2 x 12V	63-9-365-1 (Wet)	1.5	13.13 / 334	6.88 / 175	9.38 / 238	67 / 30
	24V	115	2 x 12V	23-9-282-1 (Dry)	2.5	13.13 / 334	6.75 / 171	9.38 / 238	59 / 27
	24V	115	2 x 12V	23-9-211-1 (Wet)	2.5	13.13 / 334	6.75 / 171	9.38 / 238	59 / 27
<b>Wrangler 2625 DB /</b> 20.5 L x 15.5 W x 11 H 521 L x 394 W x 279 H	24V	225	4 x 6V	33-9-036-1 (Wet)	4	10.25 / 260	7.13 / 181	10.5 / 267	64 / 29
	24V	225	4 x 6V	33-9-098-1 (AGM)	3.25				
	24V	225	4 x 6V	33-9-095-1 (Dry)	3.25	10.25 / 260	7.13 / 181	10.5 / 267	55 / 25
	24V	200	4 x 6V	64-9-193-1 (Sealed)	3.25	10.24 / 260	7.12 / 181	10.83 / 275	59 / 27
<b>Wrangler 2730/3330 DB /</b> 25 L x 22 W x 13 H 635 L x 559 W x 330 H	36V	225	6 x 6V	33-9-036-1 (Wet)	4	10.25 / 260	7.13 / 181	10.5 / 267	64 / 29
	36V	225	6 x 6V	33-9-095-1 (Dry)	3.25	10.25 / 260	7.13 / 181	10.5 / 267	55 / 25
	36V	200	6 x 6V	64-9-193-1 (Sealed)	3.25	10.24 / 260	7.12 / 181	10.83 / 275	59 / 27
	36V	225	6 x 6V	33-9-098-1 (AGM)	3.25				
	36V	325	6 x 6V	26-9-150-1 (Wet)	5	12.25 / 311	7.19 / 183	14.5 / 368	105 / 48
	36V	325	6 x 6V	26-9-095-1 (Dry)	5	12.25 / 311	7.19 / 183	14.5 / 368	84 / 38
	36V	305	6 x 6V	33-9-099-1 (AGM)	5	11 / 279	7 / 178	15 / 381	
	36V	395	6 x 6V	76-9-140-1 (Wet) Needs Lester off-board battery charger	6	12.19 / 310	7.19 / 183	16.5 / 419	121 / 55
	36V	395	6 x 6V	76-9-142-1 (Dry) Needs Lester off-board battery charger	6	11.62 / 295	7 / 178	16 / 406	105 / 48
<b>Champ 2929 /</b> 26 L x 22 W x 17 H 660 L x 559 W x 432 H	36V	225	6 x 6V	33-9-036-1 (Wet)	4	10.25 / 260	7.13 / 181	10.5 / 267	64 / 29
	36V	225	6 x 6V	33-9-098-1 (AGM)	3.25				
	36V	325	6 x 6V	26-9-095-1 (Dry)	4	12.25 / 311	7.19 / 183	14.5 / 368	84 / 38
	36V	325	6 x 6V	26-9-150-1 (Wet)	4	12.25 / 311	7.19 / 183	14.5 / 368	105 / 48
	36V	305	6 x 6V	33-9-099-1 (AGM)	4	11 / 279	7 / 178	15 / 381	

Model/ Battery Compartment Size	System	Amp Hour	Battery Quantity	Part # (Type)	Approximate Run Time	Length (Inches/ Millimeters)	Width (Inches/ Millimeters)	Height (Inches/ Millimeters)	Weight (Pounds/ Kilograms)
<b>Champ 3329 /</b> 26 L x 22 W x 17 H 660 L x 559 W x 432 H	36V	325	6 x 6V	26-9-095-1 (Dry)	4	12.25 / 311	7.19 / 183	14.5 / 368	84 / 38
	36V	325	6 x 6V	26-9-150-1 (Wet)	4	12.25 / 311	7.19 / 183	14.5 / 368	105 / 48
	36V	305	6 x 6V	33-9-099-1 (AGM)	4	11 / 279	7 / 178	15 / 381	
<b>Champ 3529 /</b> 26 L x 22 W x 17 H 660 L x 559 W x 432 H	36V	225	6 x 6V	33-9-036-1 (Wet)	4	10.25 / 260	7.13 / 181	10.5 / 267	64 / 29
	36V	225	6 x 6V	33-9-098-1 (AGM)	3.25				
	36V	325	6 x 6V	26-9-095-1 (Dry)	4	12.25 / 311	7.19 / 183	14.5 / 368	84 / 38
	36V	325	6 x 6V	26-9-150-1 (Wet)	4	12.25 / 311	7.19 / 183	14.5 / 368	105 / 48
	36V	305	6 x 6V	33-9-099-1 (AGM)	4	11 / 279	7 / 178	15 / 381	
	36V	395	6 x 6V	76-9-140-1 (Wet) Needs Lester off-board battery charger	5	12.19 / 310	7.19 / 183	16.5 / 419	121 / 55
	36V	395	6 x 6V	76-9-142-1 (Dry) Needs Lester off-board battery charger	5	11.62 / 295	7 / 178	16 / 406	105 / 48
<b>Charger 2717 DB /</b> 25 L x 22 W x 14 H 635 L x 559 W x 356 H	36V	325	6 x 6V	26-9-150-1 (Wet)	4	12.25 / 311	7.19 / 183	14.5 / 368	105 / 48
	36V	325	6 x 6V	26-9-095-1 (Dry)	4	12.25 / 311	7.19 / 183	14.5 / 368	84 / 38
	36V	305	6 x 6V	33-9-099-1 (AGM)	4	11 / 279	7 / 178	15 / 381	
<b>Charger 2717 AB /</b> 25 L x 22 W x 14 H 635 L x 559 W x 356 H	36V	225	6 x 6V	33-9-036-1 (Wet)	4	10.25 / 260	7.13 / 181	10.5 / 267	64 / 29
	36V	225	6 x 6V	33-9-095-1 (Dry)	3.25	10.25 / 260	7.13 / 181	10.5 / 267	55 / 25
	36V	225	6 x 6V	33-9-098-1 (AGM)	3.25				
<b>Charger 2022 DB /</b> 20.5 L x 15 W x 12 H 521 L x 381 W x 305 H	36V	225	6 x 6V	33-9-036-1 (Wet)	4	10.25 / 260	7.13 / 181	10.5 / 267	64 / 29
	36V	225	6 x 6V	33-9-095-1 (Dry)	3.25	10.25 / 260	7.13 / 181	10.5 / 267	55 / 25
	36V	225	6 x 6V	33-9-098-1 (AGM)	3.25				
<b>Charger 2022 ABLT /</b> 22 L x 20.5 W x 12 H 559 L x 521 W x 305 H	24V	225	4 x 6V	33-9-036-1 (Wet)	4	10.25 / 260	7.13 / 181	10.5 / 267	64 / 29
	24V	225	4 x 6V	33-9-095-1 (Dry)	3.25	10.25 / 260	7.13 / 181	10.5 / 267	55 / 25
	24V	225	4 x 6V	33-9-098-1 (AGM)	3.25				
<b>Manta RS 36 / Two Batt. Trays</b> 13.5 L x 7 W x 10 H each 343 L x 178 W x 254 H each	24V	130	2 x 12V	63-9-365-1 (Wet)	3	13.13 / 334	6.88 / 175	9.38 / 238	67 / 30
	24V	130	2 x 12V	63-9-512-1 (Dry)	3	13.13 / 334	6.88 / 175	9.38 / 238	56 / 25
<b>Sidewinder 27 MB /</b> 13.5 L x 7 W x 10 H 343 L x 178 W x 254 H	12V	130	1 x 12V	63-9-365-1 (Wet)	3	13.13 / 334	6.88 / 175	9.38 / 238	67 / 30
	12V	130	1 x 12V	63-9-512-1 (Dry)	3	13.13 / 334	6.88 / 175	9.38 / 238	56 / 25