



Pacer 12/15 UE

12 and 15-inch Single-Motor
Upright Vacuums



The Pacer 12/15 UE upright was designed to deliver value to your facility maintenance program on every conceivable level.

- **Performance** – A 1.7 HP vacuum motor and 3-stage HEPA filtration
- **Proper Ergonomics** – Adjustable handle height, ergonomic grip, transport handle and foam grip high up cleaning tube
- **Intuitive Use** – All the important touch points are colored green and the patented WAVE-LOK® filter bag and alignment mechanism assures the filter bag is securely installed every time.
- **IAQ Compliance** – CRI Seal of Approval, gold rating. Meets all requirements of the LEED-EBOM standard.
- **Ease of Maintenance** - No tools required to replace brush or cord. Full bag indicator light. Thermally protected motor. Mechanical clutch protects brush and belt, if jammed. Patented WAVE-LOK® filter bag and alignment mechanism allows for easy bag removal, even if overfilled.
- **Versatility** – Low profile for easy vacuuming underneath furniture and fixtures. Extension wand reaches over 10' above the floor. 3" round brush and 10" crevice tool with onboard storage.

NSS Enterprises, Inc.
3115 Frenchmens Road
Toledo, Ohio 43607-2958
USA
www.nss.com



Printed on Green Seal® certified paper that contains 30% recycled post-consumer fiber.

Pacer 12/15 UE Specifications

Brush	Chevron style brush
Motor	2-stage, 9 amps @ 120V
Type	1.7 HP (1260 watts)
Air Flow	Maximum 100 CFM (47 l/sec)
Waterlift	92 in
Filtration	3-stage — Top-filled, two-ply poly-lined filter bag, motor filter, and HEPA exhaust filter
Switches & Controls	Rocker on/off switch and bag full indicator light
Cord	40 ft (12 m) 16-3 SJT safety yellow, also available 25-ft cord (Pacer 12 H)
Construction	Composite Polypropylene body and base
Bag Capacity	5.0 quarts dry (5.5 l)
Cleaning Path	
12 UE	12 in (30 cm)
15 UE	15 in (38 cm)
Sound Level	67 dBA (ISO 11201)
Total Vibration	1.96 m/s ² (ISO 5349-1)
Dimensions	
Height	48.75 in (125 cm)
Width 12 UE	12.5 in (32 cm)
Width 15 UE	15.5 in (39 cm)
Weight 12 UE	19 lbs (8.6 kg)
Weight 15 UE	19.6 lbs (8.9 kg)
Shipping Weight	23 lbs (10.4 kg) max
Warranty	2 years, including belt, excluding wear items
Productivity	12 UE 2,239 sq ft per hour (208 m ²) 15 UE 2,799 sq ft per hour (260 m ²)



- 1 Enclosed handle allows for a relaxed grip during operation.
- 2 Built-in extension hose and wand make above-the-floor cleaning a snap.
- 3 Patented WAVE-LOK® ensures secure bag installation every time. WAVE-LOK also ensures easy bag removal, even if overfilled.
- 4 Brush adjustment dial on the base allows for instant carpet pile adjustments.
- 5 Chevron-style brush is built for tough commercial use, and is easily removed for replacement.
- 6 Shock-absorbing wheels keep the vacuum quiet on rough surfaces.
- 7 The handle is adjustable for different height operators.
- 8 "Pig tail" type cord connection makes changing power cord easy.
- 9 A mechanical clutch protects the drive belt from breaking if the brush gets jammed.

WAVE-LOK®

The patented WAVE-LOK® filter bag and alignment mechanism ensures secure bag installation every time. WAVE-LOK eliminates dirt and dust leakage due to improper bag installation. WAVE-LOK also ensures easy bag removal, even if overfilled.

US Patent 8,439,997, D664317
Trademark 85/328511



NSS Enterprises, Inc.
3115 Frenchmens Road
Toledo, OH 43607-2958
USA

P: (800) 677-1663
F: (419) 531-3761

mailus@nss.com
www.nss.com

Specifications subject to change without notice.

DISTRIBUTED BY