



Thoroughbred for Marble and Stone

Heavy-Duty Floor Machine



The Thoroughbred For Marble And Stone floor machine sets the pace for floor machines with its tough, heavy-duty construction. An aggressive power plant, partnered with a precision gear train, gives the Thoroughbred the balance, dependability and power necessary to tackle marble and stone floor care. This rotary floor machine — because of the addition of three 10-pound (4.5 kg) weights to its deck — also has the brush pressure necessary for heavy-duty floor stripping jobs.

- The Thoroughbred offers a 1.5 HP (1.5 HP and 2 HP in 240V.) motor size that allows you to match the machine's muscle to the requirements of the job.
- Straight-line planetary gear system provides efficient transfer of power from the 66-frame motor to the floor, assuring smooth, quiet, trouble-free operation.
- This Thoroughbred floor machine is available in a 17-in. (43.2 cm) width.
- The Thoroughbred For Marble And Stone machine features a mechanical lock-out that must be released before the switch lever can be activated. This safety feature prevents unauthorized operation of the Thoroughbred if the machine is temporarily left unattended in a public place.

NSS Enterprises, Inc.
3115 Frenchmens Road
Toledo, Ohio 43607-2958
USA
www.nss.com



Printed on Green Seal® certified paper that contains 30% recycled post-consumer fiber.

Thoroughbred For Marble And Stone Specifications

Pad Size	17 in (43 cm)
Pad Speed	175 RPM
Motor	
HP	1.5 HP or 2 HP
Speed	1700 RPM (Not pad speed)
Type	66-frame, dual capacitor
Voltage	110-120V, 220-240V available
Current	
1.5 HP	14.8 amps @ 120V, 7.5 amps @ 240V
2 HP	10 amps @ 240V
Overload Protection	20-amp circuit breaker
Gearbox	11:1 ratio, 3-idler planetary gear
Cord	50 ft (15 m) 14-3 SJT safety yellow
Wheels	5 in (13 cm) non-marking
Sound Level	68 dBA
Dimensions	
Length	24 in (61 cm)
Width	18 in (46 cm)
Height	49 in (124 cm)
Weight (Machine)	
17 in 1.5 HP	140 lbs (63.6 kg)
17 in 2 HP	145 lbs (65.9 kg)
Weight (Shipping)	
17 in 1.5 HP	152 lbs (69 kg)
17 in 2 HP	157 lbs (71.3 kg)
Shipping Class	125
Warranty	1 year warranty
Productivity	1,923 sq ft per hour (179 sq m)



DO NO HARM™

Optional 4-gallon solution tank is easily attached to the machine handle—no tools necessary.



NSS Enterprises, Inc.
3115 Frenchmens Road
Toledo, OH 43607-2958
USA

P: (800) 677-1663
F: (419) 531-3761

mailus@nss.com
www.nss.com

Specifications subject to change without notice.



- 1 Dual switch levers allow the operator to easily control the side-to-side movement of the machine.
- 2 Heavy-duty metal strain relief and internal compression lock keep the cord secure.
- 3 Sturdy 1.5-in tube handle is chrome plated to resist corrosion.
- 4 Heat-treated, aircraft-grade aluminum tube clamp holds the handle firmly in place during operation.
- 5 Precision-cast aluminum locking lever lets the operator adjust the handle to a comfortable position.
- 6 5-in rear transport wheels make the Thoroughbred easy to move.
- 7 Heavy, polished aluminum motor mount casting provides a solid foundation, assuring smooth operation.
- 8 Three 10-pound (4.5 kg) 'horse-collar' weights provide additional brush pressure required to clean marble floors.
- 9 The polished aluminum skirt casting stabilizes the machine, maximizing cleaning efficiency.

DISTRIBUTED BY