

Rally 1200

12-Gallon Dual Surface Cleaner

GENERAL	The machine shall be a 12-gallon, dual surface cleaner, used as a hard floor cleaner at 1200 PSI or as a carpet extractor at 500 PSI.
CONSTRUCTION	The body shall be rotomolded polyethylene, with 12-gallon (45.5 l) recovery and 12-gallon (45.5 l) solution tanks.
CORD	Dual 25-ft (7.6 m) power cords shall be provided, conductor gauge 12-3 SJTW.
SOLUTION PUMP	The machine shall have a positive displacement pump, variable from 500 to 1200 PSI.
VACUUM MOTOR	The machine shall have one 2-stage, 2.1 HP vacuum motors with 140-in of water lift.
MAIN WHEELS	The machine shall have two, non-marking 10-in. (25.4 cm) rear wheels and two front casters for easy maneuverability and stair transport.
FLOAT SHUTOFF	The machine shall have a ball float shut-off mechanism.
SWITCHES	Two rocker switches with international symbols shall be provided - a vacuum switch and a pump switch.
HOSE CONNECTORS	Garden hose fittings shall be included for continuous use during hard surface cleaning.
SOUND LEVEL	The machine shall be capable of running at 75 dBA.
DIMENSIONS	Weight: 150 lbs. (68 kg) Length: 26 in (66 cm) Width: 17 in (43 cm) Height: 39 in (99 cm)
WARRANTY	The machine shall have a 1 year limited warranty against defects in material and workmanship.
ISO 9000	The manufacturer must be ISO 9001 registered.

Features & Benefits

Demonstration Guide

Competitive Comparison

Bid Specifications

Recommended Parts Stock

Supplemental Price List



Integrity at work.