

Rally 220

12-Gallon Tank Extractor

GENERAL	The machine shall be a 12-gallon, compact cold-water tank extractor.
CONSTRUCTION	The body shall be high density rotomolded polyethylene, with 12-gallon (45.5 l) recovery and 12-gallon (45.5 l) solution tanks.
CORD	A 25-ft (7.6 m) power cord shall be provided, rated 12-3 SJTW.
SOLUTION PUMP	The machine shall have a diaphragm-type, 220 PSI pump.
VACUUM MOTOR	The machine shall have two 2-stage 1.25 HP vacuum motors with 84-in water lift.
MAIN WHEELS	The machine shall have two, non-marking 10-in. (25.4 cm) rear wheels and two front casters for easy maneuverability and stair transport.
FLOAT SHUTOFF	The machine shall have a ball float shut-off mechanism.
SWITCHES	Three large rocker switches with international symbols shall be provided - two vacuum switches and a pump switch.
SOUND LEVEL	The machine shall be capable of running at 75 dBA.
DIMENSIONS	Weight: 86 lbs. (39 kg) Length: 26 in (66 cm) Width: 17 in (43 cm) Height: 39 in (99 cm)
WARRANTY	The machine shall have a 1 year limited warranty against defects in material and workmanship.
ISO 9000	The manufacturer must be ISO 9001 registered.

Features & Benefits

Demonstration Guide

Competitive Comparison

Bid Specifications

Recommended Parts Stock

Supplemental Price List



Integrity at work.