

Rally 220H

12-Gallon Tank Extractor

GENERAL	The machine shall be a 12-gallon, compact hot-water tank extractor.
CONSTRUCTION	The body shall be high density rotomolded polyethylene, with 12-gallon (45.5 l) recovery and 12-gallon (45.5 l) solution tanks.
CORD	Dual 25-ft (7.6 m) power cords shall be provided, 12-3 SJTW.
SOLUTION PUMP	The machine shall have a diaphragm-type, 220 PSI pump.
VACUUM MOTOR	The machine shall have two 2-stage 1.25 HP vacuum motors with 84-in water lift.
MAIN WHEELS	The machine shall have two, non-marking 10-in (25.4 cm) rear wheels and two front casters for easy maneuverability and stair transport.
FLOAT SHUTOFF	The machine shall have a ball float shut-off mechanism.
SWITCHES	Four large rocker switches with international symbols shall be provided – two vacuum switches, pump switch and heater switch.
HEATING ELEMENT	A 2000 Watt inline heater shall be provided.
SOUND LEVEL	The machine shall capable of running at 75 dbA.
DIMENSIONS	Weight: 106 lbs. (48 kg) Length: 26 in (66 cm) Width: 17 (43 cm) Height: 39 in (99 cm)



Integrity at work.®

Features & Benefits

Demonstration Guide

Competitive Comparison

Bid Specifications

Recommended Parts Stock

Supplemental Price List

Rally 220H

12-Gallon Tank Extractor

(Bid Specifications continued)

WARRANTY

The machine shall have a 1 year limited warranty against defects in material and workmanship.

ISO 9000

The manufacturer must be ISO 9001 registered.

Features &
Benefits

Demonstration
Guide

Competitive
Comparison

**Bid
Specifications**

Recommended
Parts Stock

Supplemental
Price List



Integrity at work.