

Alpha 24

24-Gallon Wet/Dry Vacuum

GENERAL	The machine shall be an industrial, tank-type dual vacuum cleaner with a tool kit, designed for wet/dry recovery.
MOTOR	The motor shall be a two-stage bypass-type motor. The single-motor horsepower shall be 1.34 HP (1,000 watts). The tank deflector shall cyclonically separate dirt and direct it to the bottom of the tank so as to maintain maximum suction through a job. The motor shall have a float shut-off device which activates to protect vacuum motor fans.
WATERLIFT	The closed waterlift shall be 94 in (239 cm).
CFM	The CFM shall be 106 in (269 cm) at 1.5 in orifice.
TANK CAPACITY	The recovery capacity shall be 2.0 dry bushel (70 l) and 24 gal (90 l) wet. The tank shall be constructed of heavy-duty polyethylene.
FILTER	The filter shall be a polyester type (which will not shrink or rot), and the filter area shall be 548 in ² (3,535 cm ²).
SOUND LEVEL	The machine shall have a sound level of 72 dBA at the operator position.
MOUNTING	The machine shall be highly maneuverable, with two 8-in (20 cm) wheels, and two 3-in (7.5 cm) casters.
CORD	The cord shall be 28 ft (8.5 m), 16-3 SJT, black.
TOOL KIT	The machine shall have a 9-piece tool kit that includes a 2-piece wand, 2-piece extension wand, 8 ft hose, crevice tool, squeegee tool, bare floor tool, and carpet tool.
DIMENSIONS	Weight: 42 lbs (19 kg) Height: 35 in (90 cm) Width: 18 in (46 cm) Length: 21 in (53 cm)

Alpha 24



Features & Benefits

Features & Benefits

Demonstration Guide

Competitive Comparison

Bid Specifications

Recommended Parts Stock

Supplemental Price List

24-Gallon Wet/Dry Vacuum

(Bid Specifications continued)

SQUEEGEE

The machine shall be available with a 31-in (79 cm) front-mounted squeegee. This squeegee will pick up in forward and reverse.

ISO 9000

The manufacturer must be ISO 9001 registered.

WARRANTY

The machine shall carry a 1-year warranty against defects in material and workmanship.



Integrity at work.®