



Bid Specs For The

bp-ranger 1450P

GENERAL	The machine shall be an industrial, tank-type internal-filter vacuum cleaner, designed for wet/dry recovery.
MOTOR	The motor shall be a 2 HP (1550 watts) by-pass type motor. The carbon brushes shall be easily accessible for inspection by removing 4 screws from the outer cover of the powerhead. The RPM working load shall be 9,990 and the heat rise shall be 40 degrees centigrade. The motor shall have a cast-aluminum motor frame and two stationary fans (baffles) with three rotating fans attached directly to the motor shaft. The suction fans and baffles shall be removable for cleaning and replacing (not an Ametek-Lamb motor). The carbon brushes shall be easily removable from their holders by removing a cap (not cartridge type), with a life of 2,000 hours per set. The armature shall be removable for service and shall have a running life of 12,000 hours, mounted on full ball bearings (each end), and housed in a steel, replaceable housing (so that in case of failure, the motor end plate and motor frame will not be scored, requiring total replacement).
POWERHEAD	The cover, motor stand, etc., shall be rotocast polyethylene. A float shut-off shall be built into the powerhead to protect the motor fans.
TANK CAPACITY	The recovery capacity shall be 14.5 gal. (55 l) wet and 1.7 bushel dry. The tank shall be constructed of rotocast polyethylene.
FILTER	The internal, removable-type filter shall have a surface area of 625 in. ² (4032 cm ²).
SOUND LEVEL	The machine shall have a sound level of 63 dbA at the operator position.
MOUNTING	The machine shall have two 10-in. (2.54 cm) diameter wheels and two 2-in. (5 cm) swivel casters. The machine shall be mounted on a tip/dispose base and handle so that the container can be tipped and wet waste emptied into a toilet.
CORD	The cord shall be 50 ft. (15 m) with an 16-3 SJT, safety yellow.
PERFORMANCE	The waterlift shall be 50 in. at .75-in. orifice, 39 in. at 1-in. orifice, 28 in. at 1.25-in. orifice, 18 in. at 1.5-in. orifice and 7.5 in. at 2-in. orifice. The CFM shall be 54.3 at .75-in. orifice, 84.8 at 1-in. orifice, 111 at 1.25-in. orifice, 130 at 1.5-in. orifice, and 146 at 2-in. orifice.

DIMENSIONS

Weight: 73 lbs. (33.1 kg)
Height: 36 in. (91.5 cm)
Width: 22.5 in. (58.1 cm)
Length: 24 in. (61 cm)

OPTION

The machine shall be available with a 27-in. (68.5 cm) front-mounted squeegee. This squeegee will pick up in forward and reverse.

UL / ULC LISTING

The machine shall be UL / ULC listed.

ISO 9000

NSS Enterprises, Inc. has been ISO 9001 registered since September 23, 1998.

WARRANTY

The machine shall have a 7-year limited warranty against defects in material and workmanship.

NSS® Enterprises, Inc.

3115 Frenchmens Road · Toledo, Ohio 43607 USA

PH 419/531 -2121 · FAX 419/531 -3761

Specifications subject to change without notice.