



Bid Specification

Colt 1050 P Wet/Dry Vacuum

GENERAL	The machine shall be an industrial, tank-type internal-filter vacuum cleaner, designed for wet/dry recovery.
MOTOR	The machine shall have a 2-stage bypass-type motor with 115V. or 220V. The horsepower shall be 1.23 HP (880 watts) and 1.6 HP at peak load.
POWERHEAD	The cover, motor stand, etc., shall be rotocast polyethylene. A float shut-off shall be built into the powerhead to protect the motor.
TANK CAPACITY	The recovery capacity shall be 10.5 gal. (40l). The tank shall be constructed of rotocast polyethylene.
FILTER	The internal, removable-type filter shall have a surface area of 625 in.2 (4032 cm2).
SOUND LEVEL	The machine shall have a sound level of 62 dbA at the operator position.
MOUNTING	The machine shall have two 10-in. (2.54 cm) diameter wheels and two 2-in. (5 cm) swivel casters. The machine shall have a front drain plug to empty the tank.
CORD	The cord shall be 35 ft. (9 m) with an 18-3 SJT, safety yellow.
PERFORMANCE	The waterlift shall be 84 in. at a closed orifice, 39.5 in. at .75-in. orifice, 25.5 in. at 1-in. orifice, 14.8 in. at 1.25-in. orifice, 8.5 in. at 1.5-in. orifice and 2.9 in. at 2-in. orifice. The CFM shall be 48.3 at .75-in. orifice, 68.4 at 1-in. orifice, 80.3 at 1.25-in. orifice, 87.8 at 1.5-in. orifice, and 92 at 2-in. orifice.
DIMENSIONS	Weight: 48 lbs. (21 kg) Height: 29 in. (73.7 cm) Width: 23 in. (58.4 cm) Length: 29 in (73.7 cm)
SQUEEGEE	The machine shall be available with an optional 27-in. (68.5 cm) front-mounted squeegee. This squeegee will pick up in forward and reverse.
UL /ULC LISTING	The machine shall be UL / ULC listed.
ISO 9000	NSS Enterprises, Inc. has been ISO 9001 registered since September 23, 1998.
WARRANTY	The machine shall have a 3-year limited warranty against defects in material and workmanship. The rotocast polyethylene parts shall be warranted for 10 years.

Specifications subject to change without notice.

NSS Enterprises, Inc. | 3115 Frenchmens Road, Toledo, OH 43551 | (419) 531-2121 | www.nss.com