



Bid Specs For The **colt** 1250S

GENERAL	The machine shall be an industrial, tank-type internal-filter vacuum cleaner, designed for wet/dry recovery.
MOTOR	The motor shall be a 2-stage by-pass type motor with 115V. or 240V. The horsepower shall be 1.23 HP (800 watts) and 1.6 HP at peak load.
POWERHEAD	The cover, motor stand, etc., shall be rotocast polyethylene. A float shut-off shall be built into the powerhead to protect the motor.
TANK CAPACITY	The recovery capacity shall be 12.5 gal. (47 l) wet and 1.5 bushel dry. The tank shall be constructed of 304 stainless steel, 22-gauge.
FILTER	The internal, removable-type filter shall have a surface area of 625 in. ² (4032 cm ²).
SOUND LEVEL	The machine shall have a sound level of 62 dbA at the operator position.
MOUNTING	The machine shall have two 10-in. (2.54 cm) diameter wheels and two 2-in. (5 cm) swivel casters. The machine shall be mounted on a tip/dispose base and handle so that the container can be tipped and wet waste emptied into a toilet.
CORD	The cord shall be 35 ft. (9 m) with an 18-3 SJT, safety yellow.
PERFORMANCE	The waterlift shall be 84 in. at a closed orifice, 39.5 in. at .75-in. orifice, 25.5 in. at 1-in. orifice, 14.8 in. at 1.25-in. orifice, 8.5 in. at 1.5-in. orifice and 2.9 in. at 2-in. orifice. The CFM shall be 48.3 at .75-in. orifice, 68.4 at 1-in. orifice, 80.3 at 1.25-in. orifice, 87.8 at 1.5-in. orifice, and 92 at 2-in. orifice.
DIMENSIONS	Weight: 63 lbs. (28.6 kg) Height: 36 in. (91.5 cm) Width: 22.5 in. (58.1 cm) Length: 24 in. (61 cm)
OPTION	The machine shall be available with a 27-in. (68.5 cm) front-mounted squeegee. This squeegee will pick up in forward and reverse.
UL /ULC LISTING	The machine shall be UL / ULC listed.

ISO 9000

NSS Enterprises, Inc. has been ISO 9001 registered since September 23, 1998.

WARRANTY

The machine shall have a 3-year limited warranty against defects in material and workmanship. The rotocast polyethylene parts shall be warranted for 10 years.

NSS® Enterprises, Inc.

3115 Frenchmens Road · Toledo, Ohio 43607 USA

PH 419/531 -2121 · FAX 419/531 -3761

Specifications subject to change without notice.