

# Galaxy 1500

## Cord-Electric Burnisher

<b>GENERAL</b>	The machine shall be a 20-in (51 cm) cord-electric, high speed floor burnisher. The machine shall have a two-piece design, shipped in two boxes and able to be sent by parcel carrier.
<b>CONSTRUCTION</b>	The machine shall have a stamped steel skirt with a non-marking vinyl bumper. The base shall consist of 11-gauge steel. The base and skirt shall be chrome-plated.
<b>PAD</b>	The machine shall have a pad speed of 1500 RPM.
<b>LOCKOUT</b>	The machine shall have a mechanical lockout lever located in the center of the switch box, which must be depressed before the switch lever will activate.
<b>CORD</b>	The cord shall be connected to the handle box. It shall be 50-ft (15.2 m) long, 14-3 ST, safety yellow with a heavy-duty plug.
<b>WHEELS</b>	The wheels shall have a 5-in (12.7 cm) diameter, be 1.375-in wide, and consist of non-marking gray rubber. The machine shall have mounted at the rear two wheels which will assist in transport.
<b>MOTOR</b>	The motor shall be 66-frame, 1.5 HP. It shall be a permanent magnet type, DC, full wave bridge rectified motor. The motor cap shall be chrome-plated for durability.
<b>TRANSMISSION</b>	The pad driver shall be driven by a heavy-duty V-belt.
<b>DIMENSIONS</b>	Weight: 97 lbs (44 kg) Length: 27 in (68.6 cm) Height: 46 in (117 cm) Width: 21 in (53.3 cm)
<b>SOUND LEVEL</b>	The machine shall operate at 69 dBA.
<b>ISO 9000</b>	The manufacturer must be ISO 9001 registered.
<b>WARRANTY</b>	The machine shall carry a 3-year warranty against defects in material and workmanship. Labor shall be carried for 1 year.

Features & Benefits

Demonstration Guide

Competitive Comparison

Bid Specifications

Recommended Parts Stock

Supplemental Price List



Integrity at work.®