



Bid Specs For The *galaxy*

- GENERAL** The machine shall be an electric, 175 RPM floor machine, available in 17 and 20-in. models. The machine shall have a two-piece design, shipped in two boxes and able to be sent by parcel carrier.
- HANDLE** The handle shall be a cylindrical tube and have a 1.25-in. diameter, and made of 14-gauge chrome-plated steel. The handle shall lock into any position within its 75-degree adjustment swing. The handle adjustment lever shall be in the proximity of the control handles. The tube handle shall have a pad-holder storage hook.
- LOCKOUT** The machine shall have a mechanical lockout lever located in the center of the switch box, which must be depressed before the switch lever will activate. The on/off trigger shall be metal, not plastic.
- CORD** The cord shall be connected to the handle box. It shall be 50-ft. (15.2 cm) long, 14-3 ST, black with a heavy-duty plug. The cord wrap shall be quick release. The cord strain relief shall be metal, not plastic.
- WHEELS** The wheels shall have a 5-in. diameter, be 1.375-in. wide, and consist of non-marking gray rubber. They shall be positioned in a wide stance to provide easy transport.
- MOTOR** The motor shall be AC, 66-frame, 1 HP or 1.5 HP.
- TRANSMISSION** The gears shall be protected by an odum coupling. The gears will be hardened steel with an 10:1 gear ratio. The gearbox cover shall not join below the grease level.
- BASE/SKIRT** The machine shall have a 11-gauge chrome-plated steel base. The skirt shall consist of 12-gauge steel, along with a non-marking vinyl bumper.
- ACCESSORIES** The machine will be adaptable for carpets and bare floors. It shall be equipped with a single cylindrical tube handle, which allows for the use of a solution tank. The skirt shall also provide an assembled tube for solution feeding to the brush or pad.
- DIMENSIONS**
- | | |
|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Weight: | 97 lbs. (44 kg) – 17-in. 100 lbs. (45.4 kg) – 20-in. 677 lbs. (307.1 kg) for a pallet (6) of 1 HP units 731 lbs. (331.6 kg) for a pallet (6) of 1.5 HP units |
| Length: | 23.5 in. (59.7 cm) – 17-in. models |

24.5 in. (62.2 cm) – 20-in. models
Height: 47 in. (119.4 cm)
Width: 18 in. (46 cm), 21 in. (53 cm)

SOUND LEVEL

The machine shall operate at a quiet 57.5 dBA.

ISO 9000

NSS Enterprises, Inc. has been ISO 9001 registered since September 23, 1998.

WARRANTY

The machine shall carry a 3-year warranty against defects in material and workmanship. Labor shall be carried for 1 year.

NSS® Enterprises, Inc.
3115 Frenchmens Road · Toledo, Ohio 43607 USA
PH 419/531 -2121 · FAX 419/531 -3761
Specifications subject to change without notice.