



Bid Specs For The ***mustang*** 1500

GENERAL	The machine shall be a 20-in. (51 cm) cord-electric, high speed floor burnisher.
PAD SPEED	The machine shall have a pad speed of 1500 RPM.
HANDLE	The handle shall be a cylindrical tube and have a 1.5-in. diameter, and made of 14-gauge chrome-plated steel. The handle shall lock into any position within its 75-degree adjustment swing.
LOCKOUT	The machine shall have a mechanical lockout lever located in the center of the switch box, which must be depressed before the switch lever will activate.
CORD	The cord shall be connected to the handle box. It shall be 50-ft. (15.2 m) long, 14-3 ST, safety yellow with a heavy-duty plug.
WHEELS	The wheels shall have a 5-in. (12.7 cm) diameter, be 1.375-in. wide, and consist of non-marking gray rubber. The machine shall have mounted at the rear two wheels which will assist in transport.
MOTOR	The motor shall be 66-frame, 1.5 HP. It shall be a permanent magnet type, DC, full wave bridge rectified motor. The motor housing shall be ABS plastic.
TRANSMISSION	The pad driver shall be driven by a heavy-duty V-belt.
BASE/SKIRT	The machine shall have a stamped steel skirt with a non-marking vinyl bumper. The base shall consist of 11-gauge steel. The base and skirt shall be powder coated.
ACCESSORIES	The machine shall be available with a dust-control system that collects the powder residue which results from burnishing old floor finishes. This dust is then deposited in a filter bag on the front of the machine.
DIMENSIONS	Weight: 97 lbs. (44 kg) Length: 27 in. (68.6 cm) Height: 46 in. (117 cm) Width: 21 in. (53.3 cm)
SOUND LEVEL	The machine shall operate at 76 dbA.

- UL / ULC LISTING** The machine shall be UL / ULC listed.
- ISO 9000** NSS Enterprises, Inc. has been ISO 9001 registered since September 23, 1998.
- WARRANTY** The machine shall carry a 3-year warranty against defects in material and workmanship. Labor shall be carried for 1 year.

NSS® Enterprises, Inc.
3115 Frenchmens Road · Toledo, Ohio 43607 USA
PH 419/531 -2121 · FAX 419/531 -3761
Specifications subject to change without notice.