

# Outlaw PB

## Battery PacVac Vacuum

<b>GENERAL</b>	The machine shall be a cordless battery-powered PacVac vacuum.
<b>MOTOR</b>	The motor shall be .5 HP, 2-stage and 24V with 44 in. (112 cm) sealed waterlift.
<b>BATTERIES</b>	Two 12V, 9.5 AH NiMH batteries shall be required. A tray with an additional battery set shall be available for easy battery staging.
<b>CHARGER</b>	The charger shall be 24V and capable of quick-charging to 60% capacity in 60 minutes, and fully recharging a set of batteries in 2 hours. The charger must be capable of automatically recharging two sets of batteries.
<b>FILTRATION</b>	The machine shall have a three-stage filtration system: a pre-filter, pleated cone filter, and a final foam filter. The pleated cone filter must have 4 sq. ft. of filter media. An optional HEPA final filter shall be available.
<b>TOOLS</b>	The machine shall have a tool kit consisting of a combination hard floor/carpet tool, round brush, and crevice tool. The machine shall also have a telescoping wand to help the operator reach high areas and low areas.
<b>TRIGGER</b>	The machine shall have an instant on/off trigger, located on wand, to maximize runtime.
<b>CONSTRUCTION</b>	The body of the machine shall be constructed of rotocast polypropylene. The “backpacker” harness shall have adjustments at the shoulders, chest, and waist. The batteries shall fit at the hip level in secured pouches that are adjustable on the hip pads for maximum comfort.
<b>HOSE</b>	The machine shall have a hose connection at the housing which allows reconfiguration for left and right-handed users.
<b>SOUND LEVEL</b>	The sound level shall be no more than 65 dbA at the operator position.
<b>DIMENSIONS</b>	The machine must weigh no more than 14 lbs. without batteries and 22 lbs. with the batteries.

Features & Benefits

Demonstration Guide

Competitive Comparison

Bid Specifications

Recommended Parts Stock

Supplemental Price List



*More Than Meets The Floor*

# Outlaw PB

## Battery PacVac Vacuum

(Bid Specifications continued)

### ISO 9000

The manufacturer must be ISO 9001 registered.

### WARRANTY

The machine shall have a 3-year limited warranty.



Features & Benefits

Demonstration Guide

Competitive Comparison

**Bid Specifications**

Recommended Parts Stock

Supplemental Price List

*More Than Meets The Floor*

