

Rally 220H

12-Gallon Tank Extractor

| | |
|-----------------|---|
| GENERAL | The machine shall be a 12-gallon, compact hot-water tank extractor. |
| CONSTRUCTION | The body shall be high density rotomolded polyethylene, with 12-gallon (45.5 l) recovery and 12-gallon (45.5 l) solution tanks. |
| CORD | Dual 25-ft (7.6 m) power cords shall be provided, 12-3 SJTW. |
| SOLUTION PUMP | The machine shall have a diaphragm-type, 220 PSI pump. |
| VACUUM MOTOR | The machine shall have two 2-stage 1.25 HP vacuum motors with 84-in waterlift. |
| MAIN WHEELS | The machine shall have two, non-marking 10-in (25.4 cm) rear wheels and two front casters for easy maneuverability and stair transport. |
| FLOAT SHUTOFF | The machine shall have a ball float shut-off mechanism. |
| SWITCHES | Three large rocker switches with international symbols shall be provided - a vacuum switch, pump switch and heater switch. |
| HEATING ELEMENT | A 2000 Watt cast aluminum inline heater shall be provided. |
| THERMOSTAT | A close range bi-metallic thermostat, used to monitor water temperature, shall also be provided. |
| SOUND LEVEL | The machine shall capable of running at 75 dbA. |
| DIMENSIONS | Weight: 106 lbs. (48 kg) Length: 26 in (66 cm) Width: 17 (43 cm) Height: 39 in (99 cm) |



Integrity at work.

Features & Benefits

Demonstration Guide

Competitive Comparison

Bid Specifications

Recommended Parts Stock

Supplemental Price List

Rally 220H

12-Gallon Tank Extractor

(Bid Specifications continued)

| | |
|----------|---|
| WARRANTY | The machine shall have a 1 year limited warranty against defects in material and workmanship. |
| ISO 9000 | The manufacturer must be ISO 9001 registered. |

- Features & Benefits
- Demonstration Guide
- Competitive Comparison
- Bid Specifications**
- Recommended Parts Stock
- Supplemental Price List



Integrity at work.®