



# Bid Specs For The **Wrangler** 2016 DB

- GENERAL** The machine shall be a 20-in. (51 cm) walk-behind, battery-powered, wheel-driven automatic scrubber.
- SCRUBBING PATH** The scrubbing path shall be 20 in. (51 cm).
- VACUUM MOTOR** The vacuum motor shall be a 3-stage bypass type, with tangential discharge. The motor shall be 24V. and 0.75 HP.
- WATERLIFT** The closed waterlift shall be 56-in. (142 cm).
- BRUSH MOTOR** The brush drive motor shall be permanent magnet, 56 frame size, gear motor type. The motor shall also be 1404 RPM and 0.75 HP.
- DRIVE** The machine shall have a 24V., gear-reduced transaxle, 0.33 HP permanent-magnet motor.
- CAPACITIES** The solution tank shall be 16 gal. (60.5 l) and the recovery tank shall be 17 gal. (64.3 l).
- BRUSH/PAD** The brush/pad speed shall be 200 RPM. The pad driver shall be 18-in. (46 cm) in diameter, structural foam with a threaded pad-holding cup. The 20-in. (51 cm) brushes available shall be bassine, nylon, polish and nylon grit-filled.
- SOLUTION FLOW** The solution flow shall be activated by a manual pull at the handle bar via rigid bars. It shall be an adjustable flow with forged brass valve, PTFE seat and seals. A solenoid valve in the scrub head shall prevent solution from being dispensed when the brush is not moving. Hand removable in-line filter.
- CONSTRUCTION** The frame shall be constructed of powder-coated steel. The body and tanks shall be constructed of rotocast polyethylene.
- CASTER** The machine shall have two 4-in. (10 cm) diameter ball-bearing swivel caster at the rear of the machine.
- WHEELS** The machine shall have two 8-in. (20 cm) diameter by 2 in. (5 cm) non-marking wheels with slip-resistant rubber, strip-grip tread.
- FLOAT SHUT-OFF** The machine shall have a float shut-off mechanism, ball-type.

<b>SQUEEGEE</b>	The squeegee shall be 32 in. (81 cm) swing type. It shall be adjustable and have a 2-piece linatex blade. Squeegees shall recover in forward and reverse, and will include a breakaway feature that prevents accidental damage to fixed objects. A 35-in (89 cm) curved squeegee, heavy-duty with gum-rubber blade shall be available.
<b>DIMENSIONS</b>	Weight: 227 lbs. (103 kg) Height: 37 in. (95 cm) Length: 55 in. (139.7 cm) Width: 21 in. (53.3 cm)
<b>SOUND LEVEL</b>	The sound level shall be less than 65 dbA at the operator position.
<b>ATTACHMENTS</b>	Attachments included with the machine shall consist of a 2-piece wand, a 7-ft. (2.1 m) hose, a hose connector and a 17-in. (43.2 cm) squeegee tool.
<b>BATTERIES</b>	The machine shall have either four 6V 235 AH wet batteries, four 6V 220 AH AGM batteries, or two 12V 130 AH wet batteries.
<b>RUN TIME</b>	The 235 AH wet batteries shall run for 3.0 hours. The 220 AH AGM batteries shall run for 2.8 hours. The 130 AH wet batteries shall run for 1.2 hours.
<b>BATT. CHARGER</b>	The battery charger shall be high frequency mounted on-board, allowing the batteries to be charged anywhere an electric outlet is available.
<b>ISO 9000</b>	The manufacturer must be ISO 9001 registered.
<b>WARRANTY</b>	The machine shall carry a 3-year limited warranty against defects in material and workmanship, and 10 years on its polyethylene body.

**NSS® Enterprises, Inc.**  
3115 Frenchmens Road · Toledo, Ohio 43607 USA  
PH 419/531 -2121 · FAX 419/531 -3761  
Specifications subject to change without notice.