



NSS Enterprises, Inc.

HEAVY-DUTY WET/DRY VACUUMS

BP RANGER

For unmatched performance in heavy-duty wet/dry vacuums, the extreme performance of the BP Ranger Series is unrivaled.

- Extended-Life Vacuum Motor. The vacuum motor in the BP Ranger is designed to last longer than standard vacuum motors.
- Seven-Year Vacuum Motor Warranty.
- Tip Dispose Feature. BP Ranger vacuums have a pivot on the base allowing them to be drained into any drain, up to toilet height.
- Optional Feature, Front Mount Squeegee. BP Rangers are available with a 27-inch straight squeegee to boost productivity in large-area wet pick-up.

**BP RANGER 1450 P
WITH SQUEEGEE**



**BP RANGER 1250 S
WITH SQUEEGEE**



DO NO HARM™

The front mount squeegee helps reduce operator fatigue often associated with using a hose and wand. At 69 dbA, the BP Ranger can be used for daytime cleaning.

Printed on Green Seal® certified paper that contains 30% recycled post-consumer fiber.

SPECIFICATIONS

BP RANGER

Input Voltage	100-120V, 60 Hz		
Motor Type	2-stage bypass		
Power	2.0 HP		
Airflow	119 CFM (3.4 m ³)		
Water lift	122-in (310 cm)		
Tank Construction	1450 P	1250 S	
	Polyethylene	Stainless Steel	
Capacity	1450 P	1250 S	
	14.5 Gal (55L)	12.5 Gal (47L)	
Tool Kit	Sold Separately		
Filter Area	625 in ² (0.4 m ²)		
Cord	50 ft (15.2 m) 16-3 SJT		
Sound Level	69 dbA		
Dimensions	L	W	H
	36 in (91.5 cm)	22.5 in (58 cm)	24 in (61 cm)
Weight		1450 P	1250 S
	Machine	73 lbs (33.1 kg)	74 lbs (33.5)
	Shipping	100 lbs (45.4 kg)	101 lbs (45.8 kg)
Shipping Class	150		
Warranty	7 years parts (including vacuum motor), 10 years on rotomolded parts		



1. Rugged polyethylene tank and power head stand up to heavy-duty commercial use.
2. High air intake; float shut off activates long before any moisture reaches the vacuum motor.
3. The 2 HP vacuum motor produces the powerful performance and longevity that is the hallmark of the BP Ranger.
4. The cone surrounding the float shut-off combines with the round tank to generate cyclonic action, forcing liquid and debris to the sides and bottom of the recovery tank and away from the vacuum motor.
5. Optional 27-in front mount squeegee increases productivity by allowing quick wet recovery over large floor areas.
6. Large chemical-resistant rear wheels and front casters make the BP Ranger extremely maneuverable.
7. BP Ranger power heads are free standing. Set them on the floor and run them to circulate air through the internal chambers, completely drying them after every use.
8. Tip-dispose tank allows easy emptying into most toilets and drains.

TOOL KITS (SOLD SEPARATELY)

BP Ranger tool kits are constructed with high-quality NSS parts: brass fittings, cast aluminum tools, steel wands and durable 10-ft superflex hoses. There are NSS tool kits for any application, wet or dry, and any surface, hard or soft.



NSS ENTERPRISES, INC.

3115 Frenchmens Road
Toledo, OH 43607-2958
USA

(800) 677-1663 **TEL**

(419) 531-3761 **FAX**

info@nss.com

NSS.COM