




NSS Enterprises, Inc.

27-INCH BATTERY BURNISHER

CHARGER 2717 AB/DB

The Charger 2717 delivers a superior shine by polishing the floor at a high speed with plenty of pad pressure. Use the Charger 2717 after scrubbing to restore the “wet-look” luster of your floor finish.

- High performance. The Charger 2717 uses an optimal combination of speed and pressure to quickly restore the luster of floor finish. The powerful motor on the Charger 2717 is perfect for concrete polishing with diamond pads.
- Clean operation. The Charger 2717 captures the floor finish powder created during polishing with the efficient Vac-Trac Dust Control System built into the pad motor shroud.
- The electric advantage, low cost of ownership. Unlike propane burnishers, the Charger 2717 doesn't need frequent maintenance. Save thousands of dollars of operating costs by avoiding propane fuel costs, oil changes, and other costly repairs.



Charger 2717 DB



Pad Change Position



Charger 2717 AB



Battery burnishers get the job done without the environmental downside of propane burnishers. Quiet operation, no exhaust fumes, excellent dust collection and lower energy costs.

Printed on Green Seal® certified paper that contains 30% recycled post-consumer fiber.

SPECIFICATIONS

CHARGER 2717 AB/DB

Model	AB (Pad Assist)	DB (Wheel Drive)	
Pad Speed	1700 RPM	1700 RPM	
Pad Size	27 in (69 cm)	27 in (69 cm)	
Motor			
Type	Permanent magnet	Permanent magnet	
Voltage	36 V	36V	
Power	3.0 HP (2237W)	3.0 HP (2237W)	
Batteries	6 x 6V	6 x 6V	
Batteries			
Type and Size	220 AH AGM 235 AH Wet	330 AH AGM 350 AH Wet	
Run Time			
AGM Batteries	Up to 2.7 hours	Up to 2.7 hours	
Wet Batteries	Up to 3.0 hours	Up to 3.0 hours	
Drive System	Pad Assist	Chain drive, 0.5 HP	
Safety Switch	Tilt switch prevents operation when head is up.	Tilt switch prevents operation when head is up.	
Overload Protection	Machine controller protects the motor if current is too high.	Machine controller protects the motor if current is too high.	
Construction			
Frame	10-gauge steel	10-gauge steel	
Housing	12-gauge steel	12-gauge steel	
Flexiwall Shield	ABS with steel liner	ABS with steel liner	
Wheels	Two 10-in wheels	One 10-in drive wheel	
Casters	One 6-in caster	Two 6-in casters	
Sound Level	68 dBA	68 dBA	
Dimensions			
L x W x H	65 x 30 x 42 in 165 x 76 x 106 cm	65 x 30 x 42 in 165 x 76 x 106 cm	
Weight (Lbs)			
Machine	<u>Wet</u> 713 <u>AGM</u> 697	<u>Wet</u> 985	<u>AGM</u> 994
Shipping	786 770	1,058	1,086
Productivity (ft²/hr)	22,059 (2,049 m ² /hr)	32,342 (3,013 m ² /hr)	
Warranty	3 years parts, 1 year labor		



1. LED display shows the battery charge and displays diagnostic codes when service is needed.
2. The on-board battery charger provides convenient recharging anytime, anywhere.
3. The Vac-Trac Dust Control System collects 99.5% of dust to maintain indoor air quality.
4. The durable powder-coated 12-gauge steel body is built for heavy-duty commercial use.
5. The battery tray and drain permit quick clean-up the event that battery acid spills inside the machine.
6. The variable speed drive wheel makes the Charger 2717 DB extremely maneuverable.
7. The Flexiwall shield surrounds the pad, preventing debris from entering the pad area.
8. (Optional) Improve productivity and reduce fatigue by adding the sulky attachment. The sulky flips up and stores on the handle when not in use. (DB model only)



NSS ENTERPRISES, INC.

3115 Frenchmens Road
Toledo, OH 43607-2958
USA

(800) 677-1663 **TEL**
(419) 531-3761 **FAX**
info@nss.com

OPTIONS AND ACCESSORIES



Monitor machine use through the internet. Sentry helps you manage your fleet by reporting machine usage, charge cycles and more.

NSS.COM