



NSS Enterprises, Inc.

VARIABLE-SPEED FLOOR MACHINE

MAVERICK 300

For versatility in floor and carpet care, the Maverick 300 sets the standard for variable-speed floor machines. By dialing in the right speed, the Maverick 300 can polish, spray buff, scrub, and strip.

- Versatility. The Maverick 300 has excellent performance at speeds ranging between 200 and 310 RPM
 - Low speed applications. Scrub and strip hard floors.
 - High speed applications. Polish and spray buff hard floors. Bonnet clean carpet.
- Safety lock-out. The mechanical lock-out switch on the Maverick 300 prevents accidental starts.



The Maverick 300 can be used to spray buff and damp strip. Repair and restore worn floor finish in high traffic areas without using chemicals to strip the entire area.

Printed on Green Seal® certified paper that contains 30% recycled post-consumer fiber.

SPECIFICATIONS

MAVERICK 300

Pad Size	17 in (43 cm)	20 in (51 cm)
Pad Speed	Variable, 200 to 310 RPM	
Pad Driver	Flexible polypropylene	
Motor	DC Rectified Permanent Magnet	
Type	66	
Frame Size	115V or 240V	
Voltage	1.5 HP (1100 Watts)	
HP		
Current	15A at 115V (Typical conditions) 7.5A at 240V (Typical conditions)	
Overload Protection	Circuit Breaker	
Drive	3-idler planetary gear, 10:1 Ratio	
Construction	Polished Aluminum Skirt	
Wheels	5 in (13 cm) non-marking	
Handle	14-gage chrome plated steel	
Sound Level	63 dBA	
Safety Switch	Mechanical lock-out switch	
Cord Length	75 ft (23 m)	
Cord Type	14-3 ST Safety Yellow (115V Model) 16-3 ST Safety Yellow (240V Model)	
Dimensions (L x W x H)	26 x 22 x 49 in 66 x 56 x 124 cm	
Machine Weight	85 lbs (39 kg)	92 lbs (42 kg)
Shipping Weight	113 lbs (51 kg)	120 lbs (54 kg)
Shipping Class	125	
Warranty	3 years parts	
Productivity		
Polish	7,000 ft ² /hr (650 m ² /hr)	10,000 ft ² /hr (929 m ² /hr)
Scrub	2,700 ft ² /hr (251 m ² /hr)	3,600 ft ² /hr (334 m ² /hr)
Shampoo	1,200 ft ² /hr (111 m ² /hr)	1,430 ft ² /hr (133 m ² /hr)
Spray Buff	2,700 ft ² /hr (251 m ² /hr)	3,100 ft ² /hr (288 m ² /hr)



1. The mechanical lock-out prevents accidental activation or unauthorized use of the machine.
2. Reinforced cord strain relief prevents damage to the cord.
3. Sturdy 1.5-in tube handle is chrome-plated to resist corrosion.
4. Built-in cord wrap hook provides easy storage for the power cord when not in use.
5. Ergonomic handle adjustment allows the operator to set the handle height for comfort and control.
6. A safety-yellow vinyl bumper surrounds the Maverick's skirt to protect walls and fixtures from accidental damage.



NSS ENTERPRISES, INC.

3115 Frenchmens Road
Toledo, OH 43607-2958
USA

(800) 677-1663 **TEL**
(419) 531-3761 **FAX**
info@nss.com

OPTIONS AND ACCESSORIES

ECOSTRIP



Ecostrip 400 pads are coated with a specially formulated diamond abrasive that can remove layers of floor finish without stripping chemicals.

Ecostrip Buff pads have a fine 8500 grit diamond coating that brings back the shine after scrubbing. Perfect for high traffic areas and restoration work.



Add a 3.5 gallon solution tank to your floor machine. The solution tank easily mounts on the handle. A hand operated valve controls solution flow and a tube delivers solution directly to a port in the skirt.

NSS.COM