



NSS Enterprises, Inc.

26" WALK-BEHIND SCRUBBER

WRANGLER 2625 DB

Improve productivity with NSS's mid-sized walk-behind scrubbers. Perfect for medium and large areas in retail, healthcare, hospitality and light industrial facilities. The Wrangler 2625 DB possesses many large scrubber features in a smaller, more maneuverable design.

- Exceptional productivity. The 26" scrub deck and 25-gallon solution tank facilitate exceptional productivity with fewer trips to drain and refill the machine.
- Built for daily commercial use. The Wrangler 2625's rugged construction ensures it is ready to work when you need it.
- Simple controls. Operated by just a few switches and mechanical levers, custodians can be ready to clean with just a few minutes of training.



DO NO HARM™

Stainless steel hardware, durable steel framework and heavy-duty rotomolded tanks keep the Wrangler 2625 DB on the job, and out of the landfill, for years.

Printed on Green Seal® certified paper that contains 30% recycled post-consumer fiber.

SPECIFICATIONS

WRANGLER 2625 DB

| | | |
|------------------------------------|--|-------------------------|
| Cleaning Path | 26 in (64 cm) | |
| Brush/Pad | 2 x 13 in | |
| Solution Tank | 25 gal (95 L) | |
| Recovery Tank | 27 gal (102 L) | |
| Solution Flow Rates | 0 to 1.0 GPM, manual valve | |
| Brush Motor (HP) | 0.75 (560 W) | |
| Brush Motor (RPM) | 200 RPM | |
| Pad Pressure | 60, 90, 120 lbs (27, 40, 54 kg) | |
| Vacuum Motor (HP) | 0.75 (560 W) | |
| Vacuum Motor (CFM) | 65 | |
| Water Lift (in) | 56 | |
| Drive Motor (HP) | 0.33 (250 W) | |
| Drive Wheel | Two 8" x 2" | |
| Wheel Material | Non-marking rubber with non-slip tread | |
| Drive Speed | Forward: 200 ft/min (61 m/min) Reverse: 125 ft/min (38 m/min) | |
| Batteries, Quantity | 4 x 6V | |
| Batteries, Type and Size | 220 AH AGM or 235 AH Wet | |
| Run Time (Hours) | Up to 3.2 hours Up to 3.5 hours | |
| 220 AH AGM | | |
| 235 AH Wet | | |
| Sound Level (dBA) | 68 dBA | |
| Productivity (ft ² /hr) | | |
| Theoretical | 25,999 (2,415 m ² /hr) | |
| Practical | 12,062 (1,120 m ² /hr) | |
| Dimensions | 55.5 x 27 x 41 in | |
| L x W x H | 141 x 69 x 104 cm | |
| Weight (Lbs) | | |
| 220 AH | Shipping 830 (376 kg) | Machine 721 (327 kg) |
| 235 AH | 717 (326 kg) | 608 (276 kg) |
| Warranty | 3 years parts, 10 years on tanks | |



1. The percolator breaks down foam, protecting the vacuum motor from damage.
2. Ergonomic handle grips and an easy to use twist throttle to control working speed.
3. An hour meter helps track regular maintenance tasks.
4. Float shut-off protects the vacuum motor from liquid or foam damage.
5. The on-board battery charger allows charging anytime, anywhere.
6. The clear solution tank hose shows the amount of cleaning solution and can be used to drain the solution tank.
7. A solenoid valve near the brush head prevents solution flow when the brushes are not moving.
8. The 32-inch squeegee swings wide on turns to leave the floor drier. The breakaway design protects the machine and facility if it catches on a surface.
9. (Optional) This scrubber comes with a Linatex squeegee blade. Natural rubber and oil-resistant Urethane squeegee blades are available as after market replacement items.



NSS ENTERPRISES, INC.

3115 Frenchmens Road
Toledo, OH 43607-2958
USA

(800) 677-1663 **TEL**
(419) 531-3761 **FAX**
info@nss.com

OPTIONS AND ACCESSORIES

SIDEKICK



Reduce chemical usage with the Sidekick Chemical Metering System. Accurately add chemicals to clean water as you use it. Zero waste. Prevents clogs in the solution tank.

SENTRY



Monitor machine use through the internet. Sentry helps you manage your fleet by reporting machine usage, charge cycles and more.

ECOSTRIP



Ecostrip 400 pads are coated with a specially formulated diamond abrasive that can remove layers of floor finish without stripping chemicals.

STRAIGHT SQUEEGEE



Straight squeegees have the ability to pick up in forward or reverse. This scrubber can be ordered with a curved or a straight squeegee.

NSS.COM